

PROTECTING PEOPLE AND ASSETS



SECURABLINDS® BLAST PLUS, FIXED GRILLE OR DOUBLE LOCK GRILLE SECURITY BLAST BLIND A4FG / A4DLG



TECHNICAL DATASHEET - A4FG / A4DLG

SECURABLINDS® BLAST PLUS, FIXED GRILLE OR DOUBLE LOCK GRILLE SECURITY BLAST BLIND



SECURABLINDS® Blast Plus, Fixed Grille or Double Lock Grille security blast blind. Internally fitted behind a buildings window for forced entry prevention and a very high level of blast protection against the effects of blast and lethal glass shrapnel.

Features and benefits:

- » SECURABLINDS® Blast Plus protection exceeds the SECURABLINDS® Blast Gate specification. The Fixed Grille has a fixed inner panel and the Double Lock Grille has a removeable inner panel.
- » In the event of an explosion, the blast blind can absorb the effects of a very high level of blast and protect against lethal glass shrapnel.
- » 6 mm polycarbonate sheet incorporated into the product acts as a trigger in closing the blind within 10 milliseconds of the blast hitting the window.
- » 85 mm polyester powder-coated aluminium blades able to rotate through 180°combining the conventional features of a window blind and the high strength of a security grille.
- » Solid construction creates an impervious barrier between a high level attack and the inside of a property.
- » Durable and resilient, with a high core strength.
- » Comprising an enhanced steel outer and inner frame, aluminium blades, high tensile rods (which create a barrier of protection), enhanced hinge blocks, enhanced stainless steel shoot bolts (A4DLG).
- » Aesthetically pleasing compared to physical security systems, appearing as a conventional window blind.

- » Does not suffer broken cords, strings or blades.
- » Easy to maintain.
- » Manufactured in accordance with ISO 9001.

Unit can be packed either side up to 37.5 mm to accommodate variable aperture sizes.

APPLICATIONS

Can be retrofitted to fit existing buildings as well as new-build applications. Predominantly to be used in window apertures fixed within the reveal. Sufficient substrate/ structure strength will be required. Consult manufacturer for details.

PRODUCT GUIDANCE - AS STANDARD

Type » A4FG - Fixed Grille.

» A4DLG - Double Lock Grille.

Finish Polyester powder-coated.

Polycarbonate 6 mm-thick, UV-coated on both sides.

Blades 85 mm aluminium blades, positioned at 75 mm centres.





TECHNICAL DATASHEET - A4FG / A4DLG

SECURABLINDS® BLAST PLUS, FIXED GRILLE OR DOUBLE LOCK GRILLE SECURITY BLAST BLIND



OPTIONS

width » A4FG Typical width: 1101 mm.

» A4DLG Typical width: 1102 mm.

» Can be adjusted in increments of ±75 mm; consult manufacturer for details. The amount of blades will

increase with larger widths.

Height » Typical height: 1800 mm.

» Lock height is variable, dependent on overall height

chosen. Consult manufacturer for details.

PRODUCT SPECIFICATION

Manufacturer

» Name: ABBEY PROTECT

» Web: www.abbeyprotect.com» Email: info@abbeyprotect.com

» Tel: +44 (0)151 3636304

» Address: The Abbey Group, Unit 4 Kirkby Bank Road,

Knowsley Industrial Park, Liverpool, Merseyside L33 7SY

Product reference » SECURABLINDS® Blast Plus, Fixed Grille Security Blast

Blind - A4FG

» SECURABLINDS® Blast Plus, Double Lock Grille

Security Blast Blind - A4DLG



